

- Fashion stores

- Pharmacies

- Petrol stations

- Small retail



PS705

Elegant & reliable



Retail shops are always in need of a good, durable and reliable on-counter scanner. Preferable for a great competitive price and with a nice design, as it will be used in line of sight.

Meet the PS705!

A winning scanner in design, price and features!

On-counter scanner

The PS705 is designed as outstanding on-counter scanner. With 6 directional scan fields, 24 scan line pattern and a superior 2000 scans per second scan rate, this scanner is offering higher performance than any other counter scanner on the market.

Flexible head and mounting

The PS705 can move its head for ultimate scanning usage. Tilt the head forwards and backwards within a 102° range to adjust the scanner to your most convenient scanning position. Also easy to accommodate objects of various sizes and shapes. With the wall mount feature this scanner also provides friendly installation for any suitable placement.

Withstands accidents

Anywhere people work, small accidents occur. This retail scanner is protected with an IP42 sealing against moisture and dust and has a built-in 1 meter shock absorption. This is the main reason why the PS705 guarantees the best durability in its class. The automatic sleep and wake-up function is not only designed for great user comfort while working at a counter. It also helps you to be 'more green' by saving electricity (and of course money).

Main Features

- Best cost/performance in its class
- Adjustable scan head can be tilted forward and backward within a 102° range
- Durable: IP42 and 1m drop
- Multiple interfaces with only a cable change
- Automatic sleep and wake-up mode
- Supports wall-mount hanging for easy installation
- STAR code reconstruction technique to scan damaged barcodes

PS705

Specifications

Operational & Performance

Technology	Laser
Light Source	650 nm Visible Laser Diode
Light level	Max 4800 LUX
Dept of field	up to 240mm @ 0.33mm/13mil, 90% PCS (Performance may be impacted by barcode quality and environmental conditions)
Scan rate	2000 scans/sec
Scan pattern	6 direction scan fields 24 lines scan pattern
Tilted	22° forward / 80° backward

Electrical

DC input to scanner	5V DC, 240mA
Power output	1.25 Watt max@ +5V DC

Symbologies

Decode Capability	UPC-A/UPC-E, EAN-8/EAN-13, Industrial 2 of 5, Codabar, Matrix 2 of 5, Code 11, Code 93, Code 32, Code 128, Standard Code 39, Full ASCII Code 39, Interleaved 2 of 5, China Postal Code, MSI Plessey Code, UK Plessey Code, EAN/UCC 128, Telepen Code, IATA Code, GS1 Databar.
-------------------	--

Operation modes

Operation mode, Standby mode

Interfaces

RS232, K/W, USB (HID and COM port emulation),
Power USB (optional)

Enclosure

Scanner dimensions	161.51mm x 94 mm x 97.71 mm (wxhxd)
Scanner weight	350g
Color	Black White (MOQ 10)

Environmental

Operating temperature	0°C to 40°C
Storage temperature	-20°C to 60°C
Relative humidity	5% - 95% non-condensing
Drop test	1m drop resistance (with cable)
Environmental sealing	IP42

Accessories

Interface cable RS232
Interface cable USB
Interface cable K/W
Interface cable Power USB
Power supply

Safety

Laser safety	IEC 825-1 (2001) Class I, US CDRH: 21CFR1040 Class II a
Electrical safety	EN60950 second edition

Warranty

2 years

EM Compatibility

EN 55022	ClassB, 2006 + A1: 2007
EN 55024	1998 + A1: 2001 + A2: 2003

Regulatory approvals

CE, FCC, RoHs compliant

Unitech Europe

Tilburg, The Netherlands
• Tel.: +31 (0)13 460 9292
• Email: Info@eu.ute.com
• Website: <http://eu.ute.com>



unitech
because we care

Unitech America

Unitech Asia Pacific

Unitech China

Unitech Europe

Unitech Japan

Unitech Taiwan